

PREMIUM COLLECTION

TECHNICAL DETAILS



PROTEGE LA PIEL DE LAS QUEMADURAS
SOLARES PARANDO MÁS DE 97% DE LOS
RAYOS UV

PROTECTS YOUR SKIN
BLOCKS MORE THAN 97% OF UV RAYS



CLASE 1 (ARTÍCULOS PARA BEBÉS)
ANTI ALERGICO – POLÍMERO INERTE

CLASS 1 (ARTICLES FOR BABIES)
NON ALLERGIC – INERT POLYMER



100% RECICLABLE
100% RECYCLABLE

Composition	100% Olefin 'COSLAN' from POLISILK
Warp & Weft Count	500 den, solution dyed
Yarns/cm Ends/Inch	22 56
Picks/cm Picks/inch	13 33
Grams/m ² Ounces/sq. yard	190 5,6
Finish	Water and oil repellent Nuva®

COLOR FASTNESS

Light Fastness UNE EN ISO 105-B02:2001 Metode 2	7 – 8 (max 8)
Fastness to rubbing UNE EN ISO 105-X12:1996	4 – 5 (max 5)
Swimming Pool water fastness UNE EN ISO 105-E03:1997	5 (max 5)

PHYSICAL CHARACTERISTICS



EXCELENTE PROTECCIÓN CONTRA LA
DEGRADACIÓN POR LA ACCIÓN DEL SOL.

EXCELLENT PROTECTION AGAINST SUNLIGHT
DEGRADATION



COLORES TINTADOS EN MASA, OFRECIENDO
GRAN SOLIDEZ. NO SE PUDRE.

SOLUTION DYED COLORS OFFERS VERY
GOOD COLOR STABILITY
ROT-PROOF



REPELENTE AL AGUA
WATER REPELLENT

	Warp	Weft
Breaking Strength UNE EN ISO 13934-1	1647 N	740 N
Tear Resistance UNE EN ISO 13937-3	73,9 N	43,18 N
Slippage Resistance (seam method) Pr EN ISO 13936-2	3 mm	3 mm
Abrasion Resistance UNE EN ISO 12947 (Part 1 & 2) Modificada según BS 2543:1995	20.000 cycles	
Pilling Resistance UNE EN ISO 12945-2	5 (max 5)	
Dimensional Change in Washing UNE EN 25077:1996	-0,4%	-0,3%
Spraytest UNE EN 24920	5 (max 5)	